

# SULLAIR TSR-20 AIR COMPRESSOR

## FOR THE RENTAL INDUSTRY

### 16 MODELS IN ONE COMPRESSOR

100–200 hp (75–160 kW) • 380–970 cfm (10.6–27.2 m<sup>3</sup>/min) • 100–175 psi (7–12.1 bar)



#### Ideal For:

Emergency air ■ Standby air ■ Supplemental air ■ Peak load sharing

#### Rugged Package Design

- Suitable for outdoor application
- Self-contained package
- Cold weather protection
- Oil field skid
- Fluid containment pan
- Bearing fluid reservoirs
- Fork lift pockets
- Heavy-duty sound-attenuated enclosure
- Easy-access doors
- Heavy-duty air inlet filter
- Air-cooled package

#### User-Friendly & Rental-Ready

- Built-in circuit breaker
- Fully automated controls
- Sullair Supervisor™ controller
- Cam lock connections
- Genuine Sullube®  
10,000-hour fluid
- Broad operating temperature range: 20–120°F (-6.7–48.9°C)
- Multi-stage air/fluid separation
- Low fluid carry-over—  
1 ppm maximum
- Spin-on fiberglass fluid filter
- Helical design drive gears



# SULLAIR®

*Always air. Always there.®*

# SULLAIR TSR-20 TECHNICAL SPECIFICATIONS

## Energy Savings

- Flange-mounted TEFC motor for efficiency
- Capacity control options:
  - Variable Speed Drive (VSD)
  - Sullair Spiral Valve



## Sullair 10-Year Diamond Warranty

Confirming the Sullair rugged design and commitment to customer satisfaction, all new lubricated stationary air compressors (with discharge pressures up to 150 psig) include comprehensive extended warranty coverage:

- 10-year air end protection
- 5-year coverage on:
  - Motor
  - Aftercooler
  - Air/fluid receiver
  - Oil Cooler
  - Variable Speed Drive (VSD)

## FREQUENCY: 60 Hz

COMPRESSOR PERFORMANCE								
Model	100L	100H	100HH	100XH	125L	125H	125HH	125XH
Motor <i>hp (kW)</i>	100 (75)	100 (75)	100 (75)	100 (75)	125 (90)	125 (90)	125 (90)	125 (90)
Capacity <i>cfm (m<sup>3</sup>/min)</i>	555 (15.5)	485 (13.6)	430 (12)	380 (10.6)	685 (19.2)	615 (17.2)	555 (15.5)	495 (13.9)
Pressure <i>psi (bar)</i>	100 (7)	125 (8.6)	150 (10.3)	175 (12.1)	100 (7)	125 (8.6)	150 (10.3)	175 (12.1)

COMPRESSOR PERFORMANCE								
Model	150L	150H	150HH	150XH	200L	200H	200HH	200XH
Motor <i>hp (kW)</i>	150 (110)	150 (110)	150 (110)	150 (110)	200 (160)	200 (160)	200 (160)	200 (160)
Capacity <i>cfm (m<sup>3</sup>/min)</i>	815 (22.8)	740 (20.7)	680 (19)	610 (17.1)	970 (27.2)	900 (25.2)	845 (23.7)	775 (21.7)
Pressure <i>psi (bar)</i>	100 (7)	125 (8.6)	150 (10.3)	175 (12.1)	100 (7)	125 (8.6)	150 (10.3)	175 (12.1)

FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.