

SULLAIR TSR-32 AIR COMPRESSOR

FOR THE RENTAL INDUSTRY

13 MODELS IN ONE COMPRESSOR

220–333 hp (164–248 kW) • 784–1600 cfm (21.9–44.8 m³/min) • 100–175 psi (7–12.1 bar)



Ideal For:

Emergency air ■ Standby air ■ Supplemental air ■ Peak load sharing

Rugged Package Design

- Suitable for outdoor application
- Self-contained package
- Cold weather protection
- Oil field skid
- Fluid containment pan
- Spill-proof base plate
- Fork lift pockets
- Heavy-duty sound-attenuated enclosure
- Easy-access doors

User-Friendly & Rental-Ready

- Built-in circuit breaker
- Fully automated controls
- Sullair Supervisor™ controller
- RS-232 and RS-485 ports for communications and remote monitoring
- Cam lock connections
- Genuine Sullube® 10,000-hour fluid
- Broad operating temperature range: 20–120°F (-6.7–48.9°C)
- Multi-stage air/fluid separation
- Low fluid carry-over—1 ppm maximum
- Spin-on fiberglass fluid filter

 **SULLAIR**[®]
Always air. Always there.[®]

SULLAIR TSR-32 TECHNICAL SPECIFICATIONS

Energy Savings

- Flange-mounted TEFC motor for efficiency
- Capacity control options:
 - Variable Speed Drive (VSD)
 - Sullair Spiral Valve



Sullair 10-Year Diamond Warranty

Confirming the Sullair rugged design and commitment to customer satisfaction, all new lubricated stationary air compressors (with discharge pressures up to 150 psig) include comprehensive extended warranty coverage:

- 10-year air end protection
- 5-year coverage on:
 - Motor
 - Aftercooler
 - Air/fluid receiver
 - Oil Cooler
 - Variable Speed Drive (VSD)

Options

- Heavy-duty air inlet filter
- Air-cooled package
- Inline filters to help meet various air quality requirements

FREQUENCY: 50 Hz & 60 Hz

COMPRESSOR PERFORMANCE								
Model	200L	200H	200HH	200XH	250L	250H	250HH	250XH
Motor <i>hp (kW)</i>	222 (166)	222 (166)	220 (164)	220 (164)	277 (207)	277 (207)	275 (205)	275 (205)
Capacity <i>cfm (m³/min)</i>	1085 (30.3)	970 (27.1)	856 (23.9)	784 (21.9)	1346 (37.6)	1225 (34.3)	1108 (31)	1000 (28)
Pressure <i>psi (bar)</i>	100 (7)	125 (8.6)	150 (10.3)	175 (12.1)	100 (7)	125 (8.6)	150 (10.3)	175 (12.1)

COMPRESSOR PERFORMANCE					
Model	300L	300H	300HH	300XH	TSR-32F (Fixed Speed)
Motor <i>hp (kW)</i>	333 (248)	333 (248)	330 (246)	330 (246)	325 (242)
Capacity <i>cfm (m³/min)</i>	1600 (44.8)	1435 (40.1)	1315 (36.8)	1225 (34.3)	1440 (40.3)
Pressure <i>psi (bar)</i>	100 (7)	125 (8.6)	150 (10.3)	175 (12.1)	125 (8.6)

DIMENSIONS & WEIGHT					
	Length <i>in (mm)</i>	Width <i>in (mm)</i>	Height <i>in (mm)</i>	Weight <i>lbs (kg)</i>	Discharge Connection <i>in (mm)</i>
	220 (5588)	84 (2134)	104 (2642)	19,900 (9026)	3 (76)

FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.