



Sullair Performance Lubricant SRF DS

For Oil Free Air Compressors



SRF DS is a high-performance, petroleum-based synthetic fluid designed specifically for oil free rotary screw compressors. This long-life, high-viscosity fluid helps improve compressor efficiency and reduce downtime—which helps you save money.

- Long-lasting – up to 8000 hours
- Excellent oxidation control
- Exceptional lubrication
- Thermally stable

Dual Antioxidant System

SRF DS is formulated with a dual antioxidant system providing optimum resistance to oil degradation. Engineered for high-temperature environments, SRF DS helps prevent overheating and optimizes compressor performance—even under heavy loads.

FEATURES AND BENEFITS

High-Viscosity Index

With a high viscosity index, SRF DS maintains a stable oil viscosity across a wide temperature range. This expert formulation provides a strong lubricating film to help extend the life of bearings and other critical components in all operating conditions—including high temperatures.

Excellent Anti-Wear Protection

Proven and tested anti-wear additives help reduce gear teeth and bearing wear—providing reliable protection for critical components in rotary screw oil free air compressors.

Long-Lasting

With select synthetic base stocks and a dual antioxidant additive system, SRF DS helps protect compressors throughout the long drain life.

Comprehensive Support

We stand ready with fluid professionals who can help with any fluid-related issues or questions. Our exclusive compressor fluid analysis program thoroughly evaluates your compressor fluid and provides critical data including: lubricant performance history, drain intervals and environmental conditions that may affect your fluid. Choosing the right fluid and testing it regularly can help you build an optimized preventive maintenance program designed to help minimize downtime.

PRODUCT INFORMATION



PACKAGING	
Size	Part Number
1 Case (4 – 1-Gallon Bottles)	1004-2857
5-Gallon Pail	1004-3003
1 Skid (32 – 5-Gallon Pails)	1004-2858

TYPICAL PROPERTIES		
Test	Units	Typical Results
Viscosity @ 40°C	cSt	34
Viscosity Index		150
Specific Gravity @15°C	g/cm ³	0.85
Flash Point	°F(°C)	385(196)
Hours		8000

SRF DS is initial gearbox fill on all new DS and DSP models.



THERE IS A COMPLETE LINE OF SULLAIR COMPRESSOR FLUIDS AVAILABLE TO MEET YOUR NEEDS.

FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.