

RDHL CONSTRUCTION & RENTAL DRYERS

600–2050 cfm (16.9–58 m³/min) • 100–175 psi (7–12.1 bar)



ENGINEERED FOR RUGGED APPLICATIONS

- Rugged druggable skid suited for the rental industry
- Pre- and after-filters with DP gauges to help achieve instrument quality air
- NEMA 4X electronics enclosure
- -40°F (-40°C) pressure dew point
- ASME VIII and CRN coded pressure vessels

Options

- Available as 12v DC or 24v DC
- Cold weather package
- Pneumatic controls
- Pneumatic motor
- Aftercooler with moisture separator and demand cycle control



SULLAIR RDHL DRYERS TECHNICAL SPECIFICATIONS

DRYER PERFORMANCE																	
Model	Flow		Flow		Flow		Flow		Inlet & Outlet Size	Weight		Length		Width		Height	
	cfm	m ³ /min	cfm	m ³ /min	cfm	m ³ /min	cfm	m ³ /min		lb	kg	in	mm	in	mm	in	mm
	100 psi	7 bar	125 psi	8.6 bar	150 psi	10.3 bar	175 psi	12.1 bar									
RDHL-600	600	16.9	660	18.6	720	20.3	775	21.9	2" NPT	2800	1270	50	1270	50	1270	90	2286
RDHL-800	800	22.6	880	24.9	960	27.1	1050	29.7	3" FLG	3600	1633	70	1778	70	1778	94	2387
RDHL-900	900	25.5	990	28	1080	30.5	1161	32.9	3" FLG	3750	1700	102	2540	75	1905	95	2413
RDHL-1000	1000	28.3	1100	31.1	1200	33.1	1300	36.8	3" FLG	4500	2041	102	2590	75	1905	95	2413
RDHL-1400	1400	39.6	1540	43.6	1680	47.5	1800	50.9	3" FLG	5200	2359	120	3048	80	2032	95	2413
RDHL-1600	1600	45.3	1760	49.8	1920	54.3	2050	58	3" FLG	5800	2631	120	3048	80	2032	95	2413

FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.