



Sullair Performance Lubricant

PristineFG™

Food Grade Fluid for Stationary Compressors



Designed for rotary screw compressors used in food, beverage and pharmaceutical applications, PristineFG is a synthetic lubricant which meets requirements for use in food processing areas.

- Meets USDA and FDA H1 requirements
- Lasts up to 6000 hours
- Reduces lubricant consumption
- Performs in wide temperature range
- Extends compressor life

A longer-life, food-grade lubricant

PristineFG gives food processors and packagers, beverage bottlers and pharmaceutical manufacturers a reliable synthetic lubricant helping extend equipment life and minimize consumption. Extensively tested for performance, consistency and regulatory compliance, it sets the standard in extending lubricant life, protecting product integrity and increasing equipment output and service life.

FEATURES AND BENEFITS

Long-lasting

PristineFG lasts up to 6000 hours — one of the longest useful lives of any food-grade lubricant available.

Performs in a wide temperature range

PristineFG is designed for maximum versatility to enhance lubrication at high and low temperatures or extreme conditions.

Resists carryover

PristineFG is formulated for low volatility and foaming resistance, resulting in reduced carryover. This means improved lubricity and extended bearing life, even in high-humidity atmospheres.

Comprehensive support

We stand ready with fluid professionals who can help with any fluid-related issues or questions. Our exclusive compressor fluid analysis program thoroughly evaluates your compressor fluid and provides critical data including: lubricant performance history, drain intervals, and environmental conditions that may affect your fluid. Choosing the right fluid and testing it regularly can help you build an optimized preventive maintenance program designed to help minimize downtime.

Call your local Sullair distributor for help in reducing your maintenance costs by standardizing on one fluid for all your rotary compressors — of any make or model.

PRODUCT INFORMATION



PACKAGING	
Size	Part Number
5 Gallon	02250196-470
55 Gallon	02250196-471

TYPICAL PROPERTIES		
Viscosity	104°F (40°C)	39.5
	212°F (100°C)	6.8
Flash Point	514°F (268°C)	
Hours	6000	



FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.