



SULLAIR SP7

OIL WATER SEPARATOR



An easy, convenient, clean and cost-effective solution to filter condensate discharge and keep your compressor room EPA compliant.

- Unique size
 - 35 lbs new and 65 lbs full
 - Easy to manage
 - Small footprint
- Maintenance free
 - No need to ever open the unit
 - No pumps, sensors, or pre-separation filter pads
 - Not susceptible to mold
 - No messy element to change
- No power consumption
 - No electricity needed
 - Internal decompression chamber
 - Place anywhere
- <10 ppm carryover
 - Separates emulsified condensate
 - Disposal as non-hazardous special waste
- Easy installation and change-out
 - Prime unit and run condensate lines directly into unit
 - Saves time and mess for service
 - When full, replace with a new unit
- Works with ALL compressor fluids
 - Manages all compressor fluids, including POLYGLYCOL and SILICONE
 - Alumina silicate substrate media bed
 - Specific gravity, emulsification, and relative humidity do not affect performance

TECHNICAL SPECIFICATIONS

FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.



COMPRESSOR HP	SP7 LIFE - HOURS
5-15	16,000
20-40	8000
50-75	6000
100-150	4000
200+	2000

SPECS	
Inlet / Outlet inches	0.25 / 0.75
Outlet inches	0.75
Height inches	25
Width / Depth inches	15
Max Flow gpm	2
Max Temp °F	125